

HLWC heaters combine robust construction with excellent design, making them ideal for both commercial and domestic use.

Efficient and long lasting

- No glare
- 1000, 1500 and 2000W
- Element life at least 10,000 hours
- Long wave IR from ceramic elements perfect for areas where no light is required
- Silent





Applications

- Churches
- **Factories**
- Garages
- **Shops** Pubs

Restaurants

Offices



HLWCB











HLWC range

| Code | Colour Watts | | IP rating |
|---------|---------------|------|-----------|
| White | | | |
| HLWC10 | White RAL9003 | 1000 | 20 |
| HLWC15 | White RAL9003 | 1500 | 20 |
| HLWC20 | White RAL9003 | 2000 | 20 |
| Black | | | |
| HLWCB10 | Black RAL9005 | 1000 | 20 |
| HLWCB15 | Black RAL9005 | 1500 | 20 |
| HLWCB20 | Black RAL9005 | 2000 | 20 |

Supplied with


- Wall bracket
- 3m white or black mains supply cable (according to paint colour)

Optional extra

Parasol clamp

Area coverage

| H (m) | X (m) | Y (m) | Z (m) | Area (m²) | |
|------------------|----------|-----------------|----------|--------------|--|
| Wall mounted | | | | | |
| 2.0 | 2.6 | 2.5 | 4.6 | 9.0 | |
| 2.5 | 3.3 | 3.3 | 5.6 | 14.6 | |
| Overhead mounted | | | | | |
| 2.0 | 2.7 | 3.8 | - | 10.2 | |
| 2.5 | 3.7 | 5.0 | - | 18.5 | |



Specifications

Voltage: 220-240V Weight: 3.5kg Lamp life: 10,000h

